

General Certificate of Education

Mathematics 6360

MM2B Mechanics 2B

Mark Scheme

2009 examination - June series

Mark schemes are prepared by the Principal Examiner and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation meeting attended by all examiners and is the scheme which was used by them in this examination. The standardisation meeting ensures that the mark scheme covers the candidates' responses to questions and that every examiner understands and applies it in the same correct way. As preparation for the standardisation meeting each examiner analyses a number of candidates' scripts: alternative answers not already covered by the mark scheme are discussed at the meeting and legislated for. If, after this meeting, examiners encounter unusual answers which have not been discussed at the meeting they are required to refer these to the Principal Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of candidates' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this Mark Scheme are available to download from the AQA Website: www.aqa.org.uk

Copyright © 2009 AQA and its licensors. All rights reserved.

COPYRIGHT

AQA retains the copyright on all its publications. However, registered centres for AQA are permitted to copy material from this booklet for their own internal use, with the following important exception: AQA cannot give permission to centres to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Set and published by the Assessment and Qualifications Alliance.

Key to mark scheme and abbreviations used in marking

Μ	mark is for method			
m or dM	mark is dependent on one or more M marks and is for method			
Α	mark is dependent on M or m marks and is for accuracy			
В	mark is independent of M or m marks and is for method and accuracy			
Е	mark is for explanation			
or ft or F	follow through from previous			
	incorrect result	MC	mis-copy	
CAO	correct answer only	MR	mis-read	
CSO	correct solution only	RA	required accuracy	
AWFW	anything which falls within	FW	further work	
AWRT	anything which rounds to	ISW	ignore subsequent work	
ACF	any correct form	FIW	from incorrect work	
AG	answer given	BOD	given benefit of doubt	
SC	special case	WR	work replaced by candidate	
OE	or equivalent	FB	formulae book	
A2,1	2 or 1 (or 0) accuracy marks	NOS	not on scheme	
–x EE	deduct <i>x</i> marks for each error	G	graph	
NMS	no method shown	c	candidate	
PI	possibly implied	sf	significant figure(s)	
SCA	substantially correct approach	dp	decimal place(s)	

No Method Shown

Where the question specifically requires a particular method to be used, we must usually see evidence of use of this method for any marks to be awarded. However, there are situations in some units where part marks would be appropriate, particularly when similar techniques are involved. Your Principal Examiner will alert you to these and details will be provided on the mark scheme.

Where the answer can be reasonably obtained without showing working and it is very unlikely that the correct answer can be obtained by using an incorrect method, we must award **full marks**. However, the obvious penalty to candidates showing no working is that incorrect answers, however close, earn **no marks**.

Where a question asks the candidate to state or write down a result, no method need be shown for full marks.

Where the permitted calculator has functions which reasonably allow the solution of the question directly, the correct answer without working earns **full marks**, unless it is given to less than the degree of accuracy accepted in the mark scheme, when it gains **no marks**.

Otherwise we require evidence of a correct method for any marks to be awarded.

Q	Solution	Marks	Total	Comments
1(a)	$\mathbf{a} = \frac{\mathrm{d}\mathbf{v}}{\mathrm{d}t} = (3t^2 - 15)\mathbf{i} + (6 - 2t)\mathbf{j}$	M1A1 A1	3	A1 (i terms) A1 (j terms)
(b)(i)	Using $\mathbf{F} = m\mathbf{a}$:			
	Force = $4 \times \{ (3t^2 - 15)\mathbf{i} + (6 - 2t)\mathbf{j} \}$	M1		
	$= (12t^2 - 60)\mathbf{i} + (24 - 8t)\mathbf{j}$	A1	2	AG
(ii)	When $t = 2$, force $= -12\mathbf{i} + 8\mathbf{j}$	M1A1		
	Magnitude of force = $\sqrt{12^2 + 8^2}$ N	M1		
	= 14.4 (N)	A1	4	
	Total		9	
2(a)	$KE = \frac{1}{2} \times 55 \times 3^2$	M1		
	= 247.5 J	A1	2	
(b)	Change in PE as slides down:			
(~)	$mgh = 55 \times 9.8 \times 20 \cos 30$	M1		Need cos 30 or sin 30
	=9335.7	A1		
	Using Conservation of Energy:			
	KE at end of slide $= 247.5 + 9335.7$	ml		$a^{+} + 9335.7$
	= 9580 J	AI		accept 9383
	Speed of Anne is $\frac{9583}{1}$	m1		
	$\sqrt{\frac{1}{2}} \times 55$			
	$= 18.7 \text{ m s}^{-1}$	A1	6	
(c)	Anne is a particle; no air resistance	E1	1	
	Total		9	

Q	Solution	Marks	Total	Comments
3(a)				
	► S			
	900			
	$\land \land $			
	22g♥ \			
	$F \blacktriangleleft$			
	4			
	71			
	Resolve vertically:			
	R = 22g + 90g	D1		
	=112g	BI		
	Using $F = \mu R$:	M1		
	F = 0.6R			
	$F = 0.6 \times 112g$	A1		$\left[\text{Needs } 0.6 \times 112 \text{g or } 0.6 \times 1097.6 \right]$
				NOT 0.6×1097 unless 658.56 seen
	=67.2g or 658.56			
	F = 659 N	A1	4	AG
				(659 must be shown from correct working)
				working)
(b)	Resolve horizontally:			
	S = F	B1		
	Momenta about 4:			
	$90g \times 5 \times \cos\theta + 22g \times 3 \times \cos\theta$			M1
	6 6 2 2 2 2	MIAI		(one term, force \times distance \times cos or sin)
	$=67.2g \times 6 \times \sin \theta$	A1		
	$450g + 66g = 403.2g \tan \theta$			
	$\tan\theta = \frac{510}{403.2}$			
	$\theta = 52.0^{\circ}$	A1	5	accept 52
			-	Alternative: or moments about <i>B</i> :
				M1 A2, 1 or 0 for four-term moment
				equation
				+ M1 for rearranging etc (dep on 4 term) + A1 for answer
	Total		9	
H				+

MM2B (cont)

MM2B (cont)				
Q	Solution	Marks	Total	Comments
4(a)	Resolving vertically: $T \cos 60 + T \cos 40 = mg$ 1.266 T = 6g	M1A1 M1		
	T = 46.4 N	A1	4	AG no marks if g deleted
(b)	Radius of circle is 0.6 tan 60 Horizontally:	B1		<i>r</i> = 1.039 or 1.04
	$\frac{mv}{r} = T\cos 50 + T\cos 30$	M1		Accept sin instead of cos for M1
	$\frac{6v^2}{1.039} = \frac{46.4\cos 50 + 46.4\cos 30}{\text{or } 70.01}$	A1		
	$v^2 = 12.123$ Speed is 3.48 m s ⁻¹	Δ1	4	
	Total		8	
5	Force acting against gravity is $mg\sin\theta$	M1		Or 147000
	Force acting against gravity and resistance is $mg\sin\theta + 200000$	m1		$200\ 000 + \operatorname{`mgsin}\theta$
	$= 600000g\sin\theta + 200000$ = 347000	A 1		
	Using power = force \times velocity	M1		
	= 347000 × 24	A1F		
	= 8330 kW	A1	6	
	1 ota		6	
6(a)	$EPE = \frac{\lambda x}{2I}$			
	180×0.8^{2}			
	$=$ 2×1.2	MI		
	= 48 J	A1	2	
(b)	Using initial EPE = KE when string becomes slack:	M1		
	$48 = \frac{1}{2} \times 5 \times v^2$	A1F		
	$v = \sqrt{\frac{96}{5}}$			
	$= 4.38 \text{ m s}^{-1}$	A1F	3	ft $\sqrt{\frac{a'}{2.5}}$
(c)	Normal reaction is 5g or 49 Frictional force is $5g \times \mu$	M1 m1A1		
	Work done by frictional force is $5\mu g \times 2$	m1		
	$= 10 \mu g$ Stong at well $\Rightarrow 10 \mu g = 49$	A1		$m1 10 \mu q - \frac{1}{q}$
	Stops at wall $\Rightarrow 10\mu g = 48$	mı		$\begin{array}{c} 111 & 10\mu g = u \\ 24 \end{array}$
	$\mu = 0.490$	A1	7	accept $\frac{27}{49}$ OE
	Total		12	

MM2B (con	<u>t)</u>			
Q	Solution	Marks	Total	Comments
7(a)	By conservation of energy to point where QP makes an angle θ with upward vertical:			
	$\frac{1}{2}mv^2 = \frac{1}{2}mu^2 - mga(1 + \sin\theta)$	M1 A1		for 3 terms, 2 KE and 1 PE $mga (1 + \sin \theta)$ term
	$v^2 = u^2 - 2ag(1 + \sin\theta)$	A1		
	Resolve radially			
	$R = \frac{mv^2}{a} - mg\sin\theta$	M1A1		M1 for 3 terms, include $\sin \theta$ or $\cos \theta$
	$=\frac{mu^2}{a}-3mg\sin\theta-2mg$	A1	6	AG
(b)	When particle leaves the track, $R = 0$ $0 = 3mg = 3mg \sin \theta = 2mg$	M1		
	$0 = 3mg = 3mg \sin \theta = 2mg$	AI		1
	$\sin\theta = \frac{1}{3}$	M1		SC3 $\sin^{-1}\frac{1}{3}$
	$\theta = 19.5^{\circ}$	A1	4	accept 19.4° or $\theta = 0.340^{\circ}$
9 (a)	$\frac{1000}{1000}$		10	
o(a)	Using $F - ma$.			
	$-\lambda m v^{\overline{2}} = m \frac{\mathrm{d}v}{\mathrm{d}t}$	M1		
	$\therefore \frac{\mathrm{d}v}{\mathrm{d}t} = -\lambda v^{\frac{3}{2}}$	A1	2	AG
(b)	$\int \frac{\mathrm{d}v}{v^{\frac{3}{2}}} = -\lambda \int \mathrm{d}t$	M1		
	$-\frac{2}{v^{\frac{1}{2}}} = -\lambda t + c$	A1		Condone no '+c'
	When $t = 0$, $v = 9 \implies c = -\frac{2}{3}$	M1 A1		Dep. on correct integration (accept sign or $\frac{1}{2}$ error)
	$\frac{2}{\sqrt{v}} = \lambda t + \frac{2}{3}$	A1		
	$\frac{\sqrt{v}}{2} = \frac{1}{\lambda t + \frac{2}{3}}$			
	$v = \left(\frac{6}{2+3\lambda t}\right)^2$	ml		Needs correct algebra
	$v = \frac{36}{\left(2 + 3\lambda t\right)^2}$	A1	7	AG
(c)	When $v = 4$,			or $\frac{36}{\left(2+3\lambda t\right)^2} = 4$ M1
	$\frac{2}{\sqrt{y}} = \lambda t + \frac{2}{3} \implies 1 = \lambda t + \frac{2}{3}$	M1A1		$\left(2+3\lambda t\right)^2 = 9 \qquad A1$
	$t = \frac{1}{2}$			$t = \frac{1}{3\lambda}$ A1 needs statement why
	3λ	A1	3	$2+3\lambda t \neq -3$
	Total		12	
L	TOTAL		75	